

Serial No. 10/656,925
60,130-1713
03MRA0069CVS

AMENDMENTS TO THE CLAIMS:

Please amend the claims as follows. This listing of claims will replace all prior listings.

1. (CURRENTLY AMENDED) A composite leaf spring comprising:
a forward leaf spring segment defining an arcuate segment;
a rearward leaf spring segment; and
a mounting segment intermediate said forward leaf spring segment and said rearward leaf spring segment, said mounting segment defining a continuously variable cross-section shape.
2. (ORIGINAL) The composite leaf spring as recited in claim 1, wherein any cross-section taken perpendicular to the mounting segment and within said mounting segment defines a substantially equivalent cross-sectional area.
3. (ORIGINAL) The composite leaf spring as recited in claim 1, wherein said mounting segment comprising a tapering width and an expanding depth such that any cross-section taken perpendicular to the mounting segment and within said mounting segment provides a singular cross-sectional shape
4. (ORIGINAL) The composite leaf spring as recited in claim 1, wherein said rearward leaf spring segment defines a first arc in a first direction and said forward leaf spring segment defines a second arc in a second direction.
5. (ORIGINAL) The composite leaf spring as recited in claim 1, wherein said forward leaf spring segment is thicker in depth than said rearward leaf spring segment.

Serial No. 10/656,925
60,130-1713
03MRA0069CVS

6. (CURRENTLY AMENDED) A suspension system comprising:
a composite leaf spring comprising a forward leaf spring segment defining an arcuate segment, a rearward leaf spring segment, and a mounting segment intermediate said forward leaf spring segment and said rearward leaf spring segment; and
an axle beam attachment system comprising a cavity engageable with said mounting segment at only a single predefined location along said mounting segment.
7. (ORIGINAL) The suspension system as recited in claim 6, wherein said mounting segment comprises a tapering width and an expanding depth such that a cross-sectional taken perpendicular to the mounting segment and within said mounting segment provides a singular cross-sectional shape.
8. (ORIGINAL) The suspension system as recited in claim 6, wherein any cross-section taken perpendicular to the mounting segment and within said mounting segment defines a cross-sectional area equivalent to any other cross-section taken perpendicular to the mounting segment within said mounting segment.
9. (ORIGINAL) The suspension system as recited in claim 6, wherein said axle attachment system comprises a mount attached to said composite leaf spring.
10. (ORIGINAL) The suspension system as recited in claim 9, wherein said mount is an integral portion of said composite leaf spring.
11. (CANCELED)

Serial No. 10/656,925
60,130-1713
03MRA0069CVS

12. (ORIGINAL) The suspension system as recited in claim 9, wherein said mount comprises an upper clamp plate and a lower clamp plate, said upper clamp plate defines a first interior cavity and said lower clamp plate defines a second interior cavity, wherein a leaf spring receipt cavity comprised of said first and second cavities corresponds to a leaf spring width and a leaf spring depth for attaching said mount at a single predetermined location along said mounting segment.

13. (ORIGINAL) The suspension system as recited in claim 6, further comprising an upper clamp plate and a lower clamp plate which defines said cavity when mounted together.

14. (ORIGINAL) The suspension system as recited in claim 13, wherein said upper clamp plate and said lower clamp plate sandwich said composite leaf spring.

15. (CURRENTLY AMENDED) A suspension system comprising:
a composite leaf spring comprising a mounting segment intermediate a forward leaf spring segment defining an arcuate segment and a rearward leaf spring segment;
and
an axle beam attachment system which interlocks at a single predetermined location along said mounting segment.

16. (ORIGINAL) The suspension system as recited in claim 15, wherein said mounting segment comprises a tapering width and an expanding depth such that any cross-section taken perpendicular to the mounting segment and within said mounting segment provides a singular cross-sectional shape.

17. (ORIGINAL) The suspension system as recited in claim 15, wherein any cross-section taken perpendicular to the mounting segment and within said mounting segment defines a cross-sectional area equivalent to any other cross-section taken perpendicular to the mounting segment within said mounting segment.

Serial No. 10/656,925
60,130-1713
03MRA0069CVS

18. (ORIGINAL) The suspension system as recited in claim 15, wherein said axle beam attachment system defines a cavity which surrounds but a singular segment within said mounting segment to interlock said axle beam attachment system with said composite leaf spring.

19. (ORIGINAL) The suspension system as recited in claim 18, further comprising a plurality of plates which define said cavity.

20. (ORIGINAL) The suspension system as recited in claim 19, wherein said plurality of plates are fastened together to define said cavity.

21. (ORIGINAL) The suspension system as recited in claim 19, further comprising an axle beam mounted to at least one of said plurality of plates.

22. (CURRENTLY AMENDED) A method of mounting an axle beam to a composite leaf spring comprising the steps of:

- (1) defining a mounting segment along a composite leaf spring comprising a tapering width and an expanding depth such that any cross-section taken perpendicular to the mounting segment and within the mounting segment provides a singular cross-sectional shape;
- (2) mechanically interlocking an axle beam attachment system with a cross-sectional shape at a single predetermined location along the mounting segment; and
- (3) mounting an axle beam to the axle beam attachment system such that the axle beam is transverse to the composite leaf spring.

23. (ORIGINAL) A method as recited in claim 22, wherein step (2) further comprises attaching an upper and lower plate together to define a cavity equivalent to the cross-sectional shape to at least partially surround and mechanically interlock the axle beam attachment system with the composite leaf spring.

Serial No. 10/656,925
60,130-1713
03MRA0069CVS

24. (ORIGINAL) A method as recited in claim 22, wherein step (2) further comprises overmolding a molded material at the single predetermined location along the mounting segment to interlock the molded material with the leaf spring.

25. (NEW) The composite leaf spring as recited in claim 1, wherein said arcuate segment defines a bend of at least ninety degrees.

26. (NEW) The composite leaf spring as recited in claim 1, wherein said mounting segment width is constantly decreasing as a mount segment depth is consistently increasing toward said rearward segment.

27. (NEW) The composite leaf spring as recited in claim 1, wherein said forward leaf spring segment is of a greater depth and of a lesser width than said rearward leaf spring segment.

28. (NEW) The composite leaf spring as recited in claim 1, wherein said rearward leaf spring segment is of constant depth and width throughout a length thereof.